



LM-200LED LED Light Meter

A professional tester specifically designed to accurately measure light output of the LED light sources.

- Lux or Foot-candle user selectable measurement units
- Measuring Range to 400,000 Lux or 40,000 Foot candles
- Built-in memory with 99 records storage
- Data Hold to freeze reading on the digital display
- MAX recording to capture highest light measurement
- Measuring lights source include all visible ranges
- Spectral response close to CIE luminous spectral efficiency
- Angled light cosine correction
- Extended length of wire for light sensor approximately 5 feet (1.5m)
- Measurements according to JISC1609:1993 and CNS 5119 general A class specifications
- Includes protective sensor cap
- Large, 3-1/2 digit display

No hassle warranty

No waiting.

*No shipping
charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



LM-200LED LED Light Meter

Data Sheet

General Specifications

| | |
|------------------------|--|
| Display | 2000 count LCD |
| Sensor | Silicon photodiode and filter. |
| Environment | Indoor operation |
| Altitude | Up to 2000m. |
| LED Light Measurement | 3½ digits, 2000 readings |
| Range | 40, 400, 4,000, 40,000, 400,000 Lux 40, 400, 4,000, 40,000 Foot-candle |
| Accuracy | +/-3% (Calibrated to standard incandescent lamp 2856° K) and corrected LED day while-light spectrum. +/-6% other visible light sources |
| Temperature / Humidity | |
| Operating | -10 °C to 40 °C (14°F to 104°F), 0 to 80 %RH. |
| Storage | -10 °C to 50 °C (14°F to 122°F), 0 to 70 %RH. |
| Power Supply | 9V NEDA 1604, IEC 6F22, JIS 006P battery |
| Battery life | 200 hours |
| Auto Power Off | approx 6 min |
| Dimension (Base) | 130 x 63 x 38 mm (5.1 x 2.5 x 1.5") |
| Dimension (Sensor) | 80 x 55 x 29 mm (3.2 x 2.2 x 1.1") |
| Weight | 220 g (.48 lb.) include battery |
| Included Accessories | Users manual, 9 volt battery |



Amprobe® Test Tools
website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe
In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2010 Amprobe Test Tools. All rights reserved.
7/2010 LM-200LED_DS Rev A